ThinkPad E570 Platform Specifications

Processor	7th Genera	ation I	ntel® Co	re™ i3 / i5 / i7 P	rocessor				Dimensions Aluminum (WxDxH): 14.92" x 10.28" x 0.94" 379mm x 261mm x 23.9mm	
	Processor # of # of Rose Frequency Max Turbo Cache Memory Processor							Processor	Billionolono	PC/ABS (WxDxH): 14.92" x 10.28" x 1.00"; 379mm x 261mm x 25.4mm
		Cores	Threads		Frequency		Controller	Graphics	Weight	From 5.07 lb (2.30kg)
	i3-6100U			2.3 GHz	-	3MB		Intel HD	Case color	LCD Rear: Black, Silver, Gold (in EMEA only black color available) Base Cover: Black
	i5-6200U			2.3 GHz	2.8 GHz	3MB	DDR4-2133	Graphics 520		Top Cover (with keyboard): Black, Silver (in EMEA only silver color available)
	i7-6500U i3-7100U	2	4	2.5 GHz 2.4 GHz	3.1 GHz	4MB			Case material	Aluminum: Aluminum display cover
	i5-7100U			2.4 GHz	3.1 GHz	3MB 3MB	DDR4-2133	Intel HD	(LCD Rear)	PC/ABS: PolyCarbonate/Acrylonitrile-Butadiene-Styrene display cover
	i7-7500U			2.7 GHz	3.5 GHz	4MB	DDH4-2133	Graphics 620	Camera	Some: HD720p resolution, fixed focus
		L	500U ar	e not available i					Audio support	HD Audio, Conexant® CX11852 codec, Dolby® Audio™ Premium / stereo speakers, 2W x 2 / dual array microphone,
Graphics	Intel HD Graphics in processor only, or									combo audio / microphone jack
G.: Gp.:::00	NVidia GeForce 940MX Graphics, 2GB DDR5 memory, or								Keyboard	UltraNav™ TrackPoint® pointing device and multi-touch with 3+2 buttons click pad ThinkLight™ None
	NVidia GeForce GTX 950M Graphics, 2GB DDR5 memory,									
	external analog monitor support via VGA DB-15 connector and digital monitor support via HDMI™ (supporting HDCP to output protected content);									
	supports dual independent displays;								Security P Security chip	Some: Fingerprint reader on the keyboard bezel, swipe sensor None Power-on password, hard disk password, supervisor password, security keyhole
	Max resolution: 1920x1080 (HDMI)@60Hz									
Memory	32GB max / 2133MHz DDR4, non-parity, dual-channel capable,									fTPM2.0: Firmware TPM 2.0, integrated in chipset
	two 260-pin SO-DIMM sockets * System clocks down for processors with lower memory controller								vPro	dTPM2.0: Discrete TPM 2.0, TCG Certified No
Display		Some: 15.6" (396mm) HD (1366x768), anti-glare, LED backlight,								Some: Li-Polymer 4-cell (32Wh)
Diopidy	220 nits, 16:9 aspect ratio, 400:1 contrast ratio								5	Some: Li-Ion 4-cell (41Wh)
	Some: 15.6" (396mm) FHD (1920x1080), anti-glare, LED backlight, IPS,								Battery life Some: Up to 5.0 hr for Li-Polymer 4-cell (32Wh) Some: Up to 7.0 hr for Li-Ion 4-cell (41Wh)	
	250 nits, 16:9 aspect ratio, 600:1 contrast ratio Some: 15.6" (396mm) FHD (1920x1080), anti-glare, LED backlight, 250 nits, 16:9 aspect ratio, 600:1 contrast ratio								AC adapter	Some: 45-watt AC adapter
										Some: 65-watt AC adapter
Multi-touch	None									Some: 90-watt AC adapter
Storage	Up to 2 drives (one M.2 SSD and one HDD)								Preload	Some: Windows 10 Pro 64 Some: No operating system Some: Windows 10 Home 64
	Some: M.2 SSD / SATA 6.0Gb/s Some: M.2 SSD / PCIe NVMe									Lenovo Companion
	Some: HDD / SATA 6.0Gb/s, 2.5" wide, removable,									Lenovo Settings
	upgradable, Active Protection System™									Microsoft Office preloaded; purely a preduct leave to activate.
Optical	Some: DV Some: Bla			mm high, remov	/able					purchase a product key to activate • McAfee® Live Safe (30-day trial)
Ethernet	Gigabit Ethernet Connection, Realtek R8111GUS								Limited warranty	1-year - depot repair service / service upgrades available
WLAN				nfigurable by mo					Mil-Spec test	None
	 Intel Dual Band Wireless-AC 8265, 2x2, Wi-Fi + BT combo adapter, M.2 Card 								Environment	EPEAT™ Gold: ENERGY STAR®: RoHS-compliant
	 QCA, Qualcomm 344A-AC, 2x2, Wi-Fi + Bluetooth combo adapter, M.2 Card 							M.2 Card	Liviloriiion	El El II Gold, El El IGT G'I/IIT ; Horio dompilant
Bluetooth™	 QCA, Qualcomm 435-AC, 1x1, Wi-Fi + Bluetooth combo adapter, M.2 Card Bluetooth wireless, integrated in Wi-Fi + Bluetooth combo adapter 							.2 Card		
WWAN	None		,	<i>y</i>					1	
SIM card	None									
Smart Card Reader None										
ExpressCard	None									
Dock Multicard Reader	None 4-in-1 reader (MMC, SD, SDHC, SDXC)									
Ports	Two USB 3.0, one USB 2.0 (Always On), VGA, HDMI, Ethernet (RJ-45), combo audio / microphone jack, optional one USB 3.1 Type-C (standard for i5, i7 models in EMEA)									
Monitor cable	optional or None	ne US	в 3.1 Ту	/pe-C (standard	tor 15, 17 n	nodels	ın EMEA)			
IVIOITILUI CADIE	INOLIG									